

CERIUM OXIDE AS AN ADDITIVE IN BIODIESEL/DIESEL FUELED INTERNAL COMBUSTION ENGINES: A CONCISE REVIEW

M. Udayakumar*, S. Sivamani, E. Devandiran

University of Technology and Applied Sciences, Salalah, Oman

ABSTRACT

Fuel and engine technologies have advanced dramatically because of ever-increasing pollution limits and need for fuel economy. Fuel additives have been used to improve engine efficiency for more than a century, but developments in direct injection gasoline engines have posed new challenges that must be solved. In today's world of economic competitiveness, the rapid depletion of fossil fuel supplies is driving a critical demand for increased internal combustion engine efficiency. Coatings have been discovered to have a substantial impact on engine efficiency in the automobile sector. The higher the operating temperature, the higher the system's efficiency. The findings of recent studies on cerium oxide as fuel additive and thermal barrier coating materials in internal combustion engines are discussed in this review article, including combustion characteristics, performance, and emissions.

Keywords: Diesel engines, Fuel additives. Engine performance, Emission characteristics

INTRODUCTION

Biofuels are the most widely used alternative fuel. [1]. Biofuels are the most well-known alternative fuels for replacing fossil fuels in internal combustion engines (biodiesel, bioethanol, biomethanol, etc.). Biofuels made from vegetable oil look to be a viable replacement for fossil fuels. They are more environmentally friendly, biodegradable, nontoxic, recyclable, and benzene-free, and their production is quite simple. [2,3].

Biofuels are created from all parts of plants, including wood, resin, leaves, and grass, using a steam distillation technology that has advantages like lower kinematic viscosity and higher calorific value, allowing for more fuel atomization and evaporation. Because of their greater efficiency, stability, durability, and cheap fuel cost, compression ignition engines were perfect for heavy-duty applications such as agriculture, industry, and transportation. [4-5]. The search for a viable alternative source of energy has been going on for a long time to find a viable solution to the issues of rapidly depleting natural oil reserves and environmental pollution caused by harmful gas emissions such as CO and NO_x from the countless automobiles that run on petrol or diesel [6]. Because of better thermal barrier coatings, future gas turbines will be able to operate at higher gas temperatures (TBCs). As a result, considerable effort is being expended in the development of innovative materials that surpass the existing industry standard, yttria-stabilized zirconia (YSZ) [7]. In diesel engines, reduced heat rejection is most effective in turbocharged engines and least useful in regularly aspirated engines. To gain better performance over a wide variety of engine loads, it's critical to pair the engine with a turbocharger. [8].

RESEARCH FINDINGS ON EFFECT OF FUEL ADDITIVES ON ENGINE PERFORMANCE:

Table 1 shows the summary of cerium oxide as fuel additive used in diesel engines from the previously published research studies.

Table 1. Summary of Cerium oxide used as fuel additives with the source of fuel

Fuel	Fuel additive	Engine coating	Findings	References
LPO biodiesel	Surfactant	NA	The stability, performance, and emissions of lemon oil emulsions were investigated. Water was used to emulsify lemon oil in varied quantities. The performance and emissions of emulsions with varying water amounts were investigated.	[9]
Diesel	CeO ₂ nanoparticle	NA	Although cerium oxide nanoparticles are used as a diesel fuel additive to reduce particulate matter emissions and increase fuel economy, their environmental fate is unclear. Cerium oxide was recovered and described from the exhaust stream	[10]

			of a diesel engine because of the combustion of diesel fuel containing the additive Envirox™, which employs suspended nanoscale cerium oxide to reduce particulate matter emissions and increase fuel efficiency.	
Lemongrass oil	CeO ₂ nanoparticle	NA	The effects of crank angle on cylinder gas pressure and heat release rate (HRR) for neat diesel, neat LGO, LGO emulsion, and LGO nano emulsion fuels have been investigated.	[11]
Jatropha biodiesel	CeO ₂ . Al ₂ O ₃ nanoparticle	NA	Due to its potential advantage of high surface area to volume ratio, acting as a catalyst for better combustion, the effect of nanoparticle as an additive in Jatropha biodiesel has been experimentally investigated in a single cylinder DI diesel engine with the goal of diluting the level of pollutants in the exhaust and improving engine performance.	[12]
Castor oil	CeO ₂ nanoparticle	NA	Experimental research looked at the performance and emission characteristics of a compression ignition engine that used cerium oxide nanoparticles as an additive in pure diesel and diesel-biodiesel-ethanol mixes.	[13]
Pure diesel	CeO ₂	NA	When cerium oxide nanoparticles and water-based ferrofluid are introduced to diesel fuel, the link between compression ignition engine performance and emission characteristics is investigated.	[14]
Jatropha biodiesel	CeO ₂	NA	In a single cylinder, four stroke DI diesel engine, an experiment is conducted to examine the performance and emission characteristics of nano particles such as Alumina (Al ₂ O ₃) and Cerium oxide (CeO ₂) as additions in Jatropha biodiesel.	[15]
Pungam oil biodiesel	CeO ₂	NA	Biodiesel derived from Calophyllum Inophyllum oil was shown to be a feasible alternative to ultra-low sulfur diesel in the study.	[16]
Jatropha biodiesel	CeO ₂	NA	To explore the possibilities of synthesized nanofuel, single-cylinder diesel engines were employed to conduct engine performance and emission tests, which demonstrated a 15 percent average reduction in NO emissions for B5 and B10 blends with 15 ppm of catalytic nanoparticle concentration.	[17]
Jatropha biodiesel	CeO ₂	NA	The performance, combustion, and emission aspects of nanoparticles dispersed test fuels are investigated in a single cylinder constant speed DI diesel engine.	[18]
Lemon grass oil	CeO ₂	NA	An experimental study of the combined impact of nanoemulsified LGO25 with DEE and EGR was performed on a single cylinder direct injection diesel engine.	[19]
Waste cooking oil	CeO ₂	NA	Low-level cerium oxide-containing water in B5 has been researched for its impact on engine performance and emission characteristics.	[20]
Diesel	CeO ₂	NA	In an experimental investigation, the performance, combustion, and emission characteristics of a diesel engine were assessed	[21]

			using cerium oxide (CeO ₂) nanoparticles as diesel fuel additives.	
Jatropha	CeO ₂	NA	The effects of additive nanoparticles on fuel characteristics, engine performance, and emissions are explored, and the injection dosage of the additive is optimized. There are also performance comparisons of the fuel with and without the additive.	[22]
Pungam oil biodiesel	CeO ₂	NA	Different types of additives, as well as different fuel qualities, are compared and discussed. Finally, in preparation for future research, the advantages and prospects of using nanofluid as an extra fuel are explained.	[23]
Ginger grass oil	CeO ₂	NA	The experiment employed a 1500rpm, four-stroke, single-cylinder, water-cooled diesel engine. The effects of a Cerium Oxide nano-additive added to Ginger grass oil-Diesel blends on brake thermal efficiency, specific fuel consumption, and exhaust pollutants were studied.	[24]
Waste cooking oil	CeO ₂	NA	The effect of iron-doped cerium oxide (FeCeO ₂) nanoparticles as a fuel additive was investigated experimentally using waste cooking oil methyl ester in a four-stroke, single-cylinder, direct injection diesel engine..	[25]
Waste cooking oil	CeO ₂	NA	An experimental trial was conducted at full engine load to evaluate the reduction in CO, NO _x , and UBHC of synthetic biodiesel based on waste cooking oil at various concentrations of CeO ₂ nanoparticles and Ce _{0.5} Co _{0.5} nano-composite oxide.	[26]
Castor oil	CeO ₂	NA	Experimentally, the performance, combustion, and emission characteristics of a variable compression ratio engine using Cerium Oxide Nanoparticles and Carbon Nanotubes as fuel-borne nanoparticles additives in Diesterol (diesel-biodiesel-ethanol) mixes are studied.	[27]
Waste cooking oil	CeO ₂	NA	At different injection timings, the performance of a biodiesel engine employing waste cooking oil biodiesel mixed with cerium oxide (CeO ₂) nanoparticles as additives was examined.	[28]
Lemon grass oil	CeO ₂	Coated with Zirconia	Lemongrass oil is used as a biofuel since it has a lower density and viscosity than diesel.	[29]
Diesel	CeO ₂	Coated zirconia	This experimental inquiry looks at the performance and emission characteristics of a single cylinder diesel engine with yttria and ceria stabilized zirconia coating on the cylinder liner and piston head.	[30]
Citron oil biodiesel	CeO ₂	Coated Zirconia	B15, B20, and B25 blends were tested for emissions and performance in a single cylinder compression ignition engine with and without TBC under the same conditions.	[31]

Lemon oil was emulsified with a water-water combination of 5% and 10%. Only stable emulsions with 5% water were tested for performance and emissions, and only stable emulsions with 10% water were examined for performance and emissions. When compared to pure lemon oil, the findings revealed that due to the micro-explosion phenomena of water, the brake thermal efficiency

improved, and the brake specific fuel consumption increased. When the calorific value of the fuel was reduced due to the addition of water, NO_x emissions dropped but HC and CO emissions increased. [9].

The use of more realistic material in future toxicity studies and modeling will be required since pure, laboratory-produced nanoscale cerium oxide is not an acceptable surrogate for cerium oxide emitted from fuel-borne catalyst applications. [10].

When compared to pure LGO, despite the minor increase in HC and CO emissions, the LGO emulsion fuel may reduce smoke and NO_x emissions and improve Brake Thermal Efficiency (BTE) and Brake Specific Energy Consumption (BSEC). [11]. Ceria nanoparticles boost brake thermal efficiency for both test fuels due to their high surface area to volume ratio, allowing for better combustion through higher atomization, faster air-mixture mixing, and faster fuel evaporation. [12].

HC emissions are minimized because cerium oxide's activation energy burns off carbon deposits within the engine cylinder at wall temperature and prevents the development of non-polar compounds on the cylinder wall. [13,14]. The cerium nano particle mixed test fuels demonstrated a significant increase in brake thermal efficiency, approaching that of pure diesel, as well as a decrease in nitric oxide, carbon monoxide, unburned hydrocarbon, and smoke emissions. [15]. The mixing quality of biodiesel spray with air can be improved by improving the design of the fuel injection system. Cerium oxide nanoparticles (CON) can be used as a nanofuel additive catalyst to aid enhance combustion efficiency. [16]. In diesel-biodiesel blends, the addition of catalytic nanoparticles has no influence on the fuel characteristics. [17].

Nanoparticles in biodiesel minimize ignition delay and enhance combustion start-up, resulting in a lower heat release rate and cylinder pressure at full load. [18]. With DEE and EGR mode, the combustion duration and ignition delay increase for nano-emulsified LGO25 fuel but decrease for nano-emulsified LGO25 fuel. [19]. According to the findings, an aqueous nano-emulsion of cerium oxide improved overall combustion quality. Fuel utilization for brakes should be accurate. [20].

CeO₂ in diesel fuel plays an important role in the dehydrogenation process at high temperatures due to its high redox capability. When nano-CeO₂ is introduced to neat diesel, the cylinder pressure steadily rises in comparison to the reference neat diesel. [21]. The flash point and viscosity of biodiesel were found to increase when cerium oxide nanoparticles were added. Hydrocarbon and NO_x emissions are greatly reduced when cerium oxide nanoparticles are used. [22]. A nanofluid is a dispersion mixture of nano-sized particles dispersed in a liquid medium. It improves heat transmission properties and promotes great energy efficiency in a wide variety of technological applications. [23]. The HC content of the blends increased as the amount of Ginger grass oil in the blends increased [24].

The reduction in NO_x emissions was 15.7 percent, however there was no change in unburned hydrocarbon (HC) emissions. Carbon monoxide (CO) emissions were reduced by up to 24.6 percent for B30 and 15.4 percent for B30 using nano-additives. The B30 with 20% FeCeO₂ outperforms the B30 with 10% FeCeO₂ in terms of cylinder pressure and emissions. [25]. The data demonstrated that when biodiesel and its mixes were burned at full engine load, both CeO₂ and Ce_{0.5}Co_{0.5} nanocomposite oxides exhibited significant decreases in CO, NO_x, and UBHC [26].

Carbon Nanotubes operate as a catalyst to speed up the burning process, resulting in a shorter ignition time and a lower heat release rate, as well as a faster peak heat release rate.[27]. By extending fuel injection time and adding nanoparticles, engine combustion may be improved while emissions are lowered. This helps to conserve diesel fuel while also lowering pollutants in the environment [28]. The BTE and BSEC of lemongrass oil coupled with cerium oxides enhances the combustion characteristics due to the increased surface area. [29]. Engine with yttria and ceria stabilized zirconia coating with varying dosing levels of CeO₂ and diesel combination as a fuel mixture shows an increase in BTE [30]. The viscosity of raw biooil is significantly reduced when CMPO is blended with diesel. The performance and emission characteristics of the aforesaid composition with TBC covering are also improved [31].

CONCLUSION:

The review article presented an overview on cerium oxide as fuel additive and thermal barrier coating materials in internal combustion engines. The following improvements were observed with the addition of fuel additives:

- ◆ Brake and indicated power increase with loading conditions.
- ◆ Friction power increases from 0 to 25% and decreases with loading condition beyond 25%.
- ◆ Brake thermal efficiency increases with loading conditions. Indicated thermal and volumetric efficiencies decrease with loading conditions.
- ◆ Specific fuel consumption and exhaust gas temperature decreases and increases with loading conditions, respectively.
- ◆ NO_x emissions increase at low and decrease at high loading conditions. CO emissions decrease at low and increase at high loading conditions.

REFERENCES:

1. Rodica Niculescu , Adrian Clenci, and Victor Iorga-Siman “Review on the Use of Diesel–Biodiesel–Alcohol Blends in Compression Ignition Engines” *Energies* (2019), 12, 1194; doi:10.3390
2. Aditiya, H.B.; Mahlia, T.M.I.; Chong, W.T.; Nur, H.; Sebayang, A.H. Second generation bioethanol production: A critical review. *Renew. Sustain. Energy Rev.* 2016, 66, 631–653
3. Zhao, L.; Zhang, X.; Xu, J.; Ou, X.; Chang, S.; Wu, M. Techno-economic analysis of bioethanol production from lignocellulosic biomass in china: Dilute-acid pretreatment and enzymatic hydrolysis of corn stover. *Energies* 2015, 8, 4096–4117.
4. Viswanathan, K., Balasubramanian, D., Subramanian, T., & Varuvel, E. G. (2019). Investigating the combined effect of thermal barrier coating and antioxidants on pine oil in DI diesel engine. *Environmental Science and Pollution Research*, 26(15), 15573-15599.
5. Viswanathan, K., Wang, S., & Esakkimuthu, S. (2020). Impact of yttria stabilized zirconia coating on diesel engine performance and emission characteristics fuelled by lemon grass oil biofuel. *Journal of Thermal Analysis and Calorimetry*, 1-13.
6. Elumalai, P. V., Annamalai, K., & Dhinesh, B. (2019). Effects of thermal barrier coating on the performance, combustion and emission of DI diesel engine powered by biofuel oil–water emulsion. *Journal of Thermal Analysis and Calorimetry*, 137(2), 593-605.
7. Clarke, D. R., & Phillpot, S. R. (2005). Thermal barrier coating materials. *Materials today*, 8(6), 22-29.
8. Azadi, M., Baloo, M., Farrahi, G. H., & Mirsalim, S. M. (2013). A review of thermal barrier coating effects on diesel engine performance and components lifetime.
9. Randive, V. S., Nashte, A. P., Katkar, O. P., & Nanthagopal, K. (2018). An investigation on performance and emission characteristics of DI diesel engine fueled with lemon peel oil and its emulsions. *Int. J. ChemTech Res.*, CODEN (USA), 98-114.
10. Dale, J. G., Cox, S. S., Vance, M. E., Marr, L. C., & Hochella Jr, M. F. (2017). Transformation of cerium oxide nanoparticles from a diesel fuel additive during combustion in a diesel engine. *Environmental science & technology*, 51(4), 1973-1980.
11. Annamalai, M., Dhinesh, B., Nanthagopal, K., SivaramaKrishnan, P., Lalvani, J. I. J., Parthasarathy, M., & Annamalai, K. (2016). An assessment on performance, combustion and emission behavior of a diesel engine powered by ceria nanoparticle blended emulsified biofuel. *Energy conversion and management*, 123, 372-380.
12. Arockiasamy, P., & Anand, R. B. (2015). Performance, combustion and emission characteristics of a DI diesel engine fuelled with nanoparticle blended jatropha biodiesel. *Periodica Polytechnica Mechanical Engineering*, 59(2), 88-93.
13. Selvan, V. A. M., Anand, R. B., & Udayakumar, M. (2009). Effects of cerium oxide nanoparticle addition in diesel and diesel-biodiesel-ethanol blends on the performance and emission characteristics of a CI engine. *J Eng Appl Sci*, 4(7), 1819-6608.
14. Ranaware, A. A., & Satpute, S. T. (2013). Correlation between effects of cerium oxide nanoparticles and ferrofluid on the performance and emission characteristics of a CI engine. *Journal of Mechanical and Civil Engineering*.
15. Prabu, A., & Anand, R. B. (2016). Emission control strategy by adding alumina and cerium oxide nano particle in biodiesel. *Journal of the Energy Institute*, 89(3), 366-372.
16. Vairamuthu, G., Sundarapandian, S., Kailasanathan, C., & Thangagiri, B. (2016). Experimental investigation on the effects of cerium oxide nanoparticle on Calophyllum inophyllum (Punnai) biodiesel blended with diesel fuel in DI diesel engine modified by nozzle geometry. *Journal of the Energy Institute*, 89(4), 668-682.
17. Sajith, V., & Mohamed Jihad, P. M. (2015). Development of stable cerium zirconium mixed oxide nanoparticle additive for emission reduction in biodiesel blends. *Research and reviews: Journal of engineering and technology*, 4(2), 23.
18. Prabu, A. (2018). Nanoparticles as additive in biodiesel on the working characteristics of a DI diesel engine. *Ain shams Engineering journal*, 9(4), 2343-2349.
19. Sathiyamoorthi, R., Sankaranarayanan, G., & Pitchandi, K. (2017). Combined effect of nanoemulsion and EGR on combustion and emission characteristics of neat lemongrass oil (LGO)-DEE-diesel blend fuelled diesel engine. *Applied Thermal Engineering*, 112, 1421-1432.
20. Khalife, E., Tabatabaei, M., Najafi, B., Mirsalim, S. M., Gharehghani, A., Mohammadi, P., ... & Salleh, M. A. M. (2017). A novel emulsion fuel containing aqueous nano cerium oxide additive in diesel–biodiesel blends to improve diesel engines performance and reduce exhaust emissions: Part I–Experimental analysis. *Fuel*, 207, 741-750.
21. Mei, D., Li, X., Wu, Q., & Sun, P. (2016). Role of cerium oxide nanoparticles as diesel additives in combustion efficiency improvements and emission reduction. *Journal of Energy Engineering*, 142(4), 04015050.
22. Sajith, V., Sobhan, C. B., & Peterson, G. P. (2010). Experimental investigations on the effects of cerium oxide nanoparticle fuel additives on biodiesel. *Advances in Mechanical Engineering*, 2, 581407.
23. Yusof, S. N. A., Sidik, N. A. C., Asako, Y., Japar, W. M. A. A., Mohamed, S. B., & Muhammad, N. M. A. (2020). A comprehensive review of the influences of nanoparticles as a fuel additive in an internal combustion engine (ICE). *Nanotechnology Reviews*, 9(1), 1326-1349.
24. Senthil Kumar, J., & Ramesh Babu, B. R. (2019). Cerium oxide nano additive impact of VCR diesel engine characteristics by using Ginger grass oil blended with diesel. *International Journal of Ambient Energy*, 1-6.
25. Hawi, M., Elwardany, A., Ismail, M., & Ahmed, M. (2019). Experimental investigation on performance of a compression ignition engine fueled with waste cooking oil biodiesel–diesel blend enhanced with iron-doped cerium oxide nanoparticles. *Energies*, 12(5), 798.
26. Akram, S., Mumtaz, M. W., Danish, M., Mukhtar, H., Irfan, A., Raza, S. A., ... & Arshad, M. (2019). Impact of cerium oxide and cerium composite oxide as nano additives on the gaseous exhaust emission profile of waste cooking oil based biodiesel at full engine load conditions. *Renewable Energy*, 143, 898-905.

27. Selvan, V. A. M., Anand, R. B., & Udayakumar, M. (2014). Effect of Cerium Oxide Nanoparticles and Carbon Nanotubes as fuel-borne additives in Diesterol blends on the performance, combustion and emission characteristics of a variable compression ratio engine. *Fuel*, 130, 160-167.
28. Kumar, S., & Dinesha, P. (2021). Combined influence of fuel injection strategy and nanoparticle additives on the performance and emission characteristics of a biodiesel fueled engine. *Cogent Engineering*, 8(1), 1939515.
29. Venkatesan, E. P., Kandhasamy, A., Sivalingam, A., Kumar, A. S., Ramalingam, K., James Thadhani Joshua, P., & Balasubramanian, D. (2019). Performance and emission reduction characteristics of cerium oxide nanoparticle-water emulsion biofuel in diesel engine with modified coated piston. *Environmental Science and Pollution Research*, 26(26), 27362-27371.
30. Shaisundaram, V. S., Chandrasekaran, M., Mohan Raj, S., & Muraliraja, R. (2020). Investigation on the effect of thermal barrier coating at different dosing levels of cerium oxide nanoparticle fuel on diesel in a CI engine. *International Journal of Ambient Energy*, 41(1), 98-104.
31. Shanmugam, M., Sathiyamurthy, S., Rajkumar, G., Saravanakumar, S., Prabakaran, S. T., & Shaisundaram, V. S. (2021). Effect of thermal barrier coating in CI engines fueled with Citrus Medica (Citron) peel oil biodiesel dosed with cerium oxide nanoparticle. *Materials Today: Proceedings*, 37, 1943-1956.