DOI : https://doi.org/10.56452/0124

[13] Caracostas, C. A., Chiou, W. A., Fine, M. E., and Cheng, H. S., 1997. Tribological Properties of Aluminium Alloy Matrix TiB2 Composite Prepared by In-Situ Processing. Metall. Mater. Trans. A, 28A, 491 502. DOI:10.1007/S11661-997-0150-2.

[14] Boq-Kong, H., Su-Jien, L., and Min-Ten, J., 1996. The Interfacial Compounds and SEM Fractography of Squeeze-Cast SiCp /6061 Al Composites. Mater. Sci. Eng., A, 206, 110 119. DOI:10.1016/0921-5093(95)09979-4.

[15] Hashim, J., Looney, L., and Hashmi, M. S. J., 1999. Metal Matrix Composites: Production by the Stir Casting Method. J. Mater.Process. Technol., 92 93, 1 7. **HTTPS://DOI.ORG/10.1016/S0924-0136(99)00118**.

[16] Radhika, N., Subramanian, R., and Venkat Prasat, S., 2011. Tribological Behaviour of Aluminium/Alumina/Graphite Hybrid Metal Techniques, Journal of Minerals & Materials Characterization & Engineering, 10, 5, 427-443. DOI:10.1108/00368791311311169.

[17] Ross, P. J., 1996. Taguchi Techniques for Quality Engineering, 2nd Edition, McGraw-Hill Book Co., New York, 23-42.

[18] Siddhartha, Patnaik, A., and Bhatt, A. D., 2011. Mechanical and Dry Sliding Wear Characterization of Epoxy-TiO2 Particulate Filled Functionally Graded Composite Materials Using Taguchi Design of Experiment, Material & De-sign, 32 (2), 615-627. **HTTPS://DOI.ORG/10.1016/J.MATDES.2010.08.011**.

[19] Basavarajappa, S., Chandramohan, G., Mahadevan, A., Thangavelu, M., Subramanian, R., and Gopalakrishnan, P., 2007. Influence of sliding speed on the dry sliding wear behaviour and the subsurface deformation on hybrid metal matrix composite. Wear 262(7/8), 1007 1012. **HTTPS://DOI.ORG/10.1016/J.WEAR.2006.10.016**.

[20] Doel, T.J.A., and Bowen P., 1996. Tensile Properties of Particulate- reinforced metal matrix composites, 655-665, **HTTPS://DOI.ORG/10.1016/1359-835X(96)00040-1**.

[21] Song, J.J., Bong, H.D., Han, K.S., 1995. Characterization of mechanical and wear properties of Al/ Al2O3/C hybrid metal matrix composites. Scripta Metall Mater, 33, 1307 13. https://doi.org/10.1016/0956-716X(95)00359-4

ACKNOWLEDGMENT

I thank department of mechanical engineering BMS College of Engineering and Vemana Institute of Technology for their kind support and motivation in completing this work.